



ArmorCo
4710 State Rd. • Ashtabula, OH 44004
1-440-992-2331
armorco.com

O. F. 200 Opaque Fiberglass

UL 752 Level 2

NOMINAL THICKNESS: 3/8"

NOMINAL WEIGHT:

4.1 lbs per square foot

AVAILABLE SIZES:

3' X 8' 4' X 8'

3' X 9' 4' X 9'

3' X 10' 4' X 10'

MAKEUP

Multiple layers of woven roving ballistic grade fiberglass cloth woven in house impregnated with a thermoset polyester resin and compressed into flat rigid sheets designed to capture projectile.

USES

Commercial, Residential, Government, Military, Banks, Credit Unions Retail, Check Cashing, Prisons, Courthouses, Police Stations, Safe Rooms, Schools, Public Safety Facilities Stadiums.

PERFORMANCE LEVEL

Underwriters Laboratory UL 752 11th Edition Standard for Bullet Resisting Equipment. One hour fire rated to ASTM E119-00a Building Construction and Materials.

AMMUNITION TESTED

.357 magnum jacketed lead soft point, 158 grain, 1,250 fps, 3 shots

INSTALLATION

Cut ArmorCo Opaque Fiberglass using ordinary carpentry tools. We suggest using RemGrit® "Grit Edge" saw blade. Install using self tapping drywall screws. Pre-drilling may be required on 1 3/16" and thicker material. Drill using high speed steel twist drills bits. We recommend that you incorporate 4" overlap strips (battens) at seams.

WARRANTY

Materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site.

Manufactured in an ISO 9001:2008 CERTIFIED Facility